


[Back to list](#)

1-1/1 [Next page](#) From 1 - 1 Count

Display format ----- Select the type of output. -----

[Display checked documents](#)
[Check All](#)
[Uncheck All](#)
☐ \*\* Result [P ] \*\* Format(P801) 2005.04.02 1/ 1

Application no/date: 1992-142087[1992/ 5/ 7]  
 Date of request for examination: [ ]  
 Accelerated examination ( )  
 Public disclosure no/date: 1993-309011  Translate [1993/11/22]  
 Examined publication no/date (old law): [ ]  
 Registration no/date: [ ]  
 Examined publication date (present law): [ ]  
 PCT application no:  
 PCT publication no/date: [ ]  
 Applicant: TERU YAMAZAKI KK  
 Inventor: YAMAZAKI TERUMASA  
 IPC: A45D 1/06  
 FI: A45D 1/06 C A45D 1/00 ,503A A45D 1/00 ,505D  
A45D 1/00 ,505G  
 F-Term: 3B037BA01,BC07,BC04  
 Expanded classification: 303,142  
 Fixed keyword:  
 Citation: [ , . . , ] ( , , )  
 Title of invention: CURLING IRON FOR HAIRDRESSING AND BEAUTY TREATMENT

Abstract: PURPOSE: To pinch hair and to straighter by non-heating by provi  
 ding vertically a guide f an elliptical ring shape for coming into contact w  
 ith and surrounding a grip energized in the opening direction of two pieces  
 of curling irons of a horizontal V-shape. CONSTITUTION: In the upper curling  
 iron part 2, a cylindrical pipe 21 made of a synthetic resin is loaded on a  
 metallic rod 20 whose root is bent 22 a little, and its curling iron part i  
 s opposed horizontally in the tip direction to a curling iron part 3 in whic  
 h a groove 30 is formed. Grips 4, 5 of a horizontal V-shape are connected so  
 as to be freely rotatable in a connecting supporting point of the end part,  
 energized in the opening direction with a spring 6, and loaded synthetic re  
 sin pipes 40, 50 improve a function of antislipping at the time of work and  
 the sense of grip. On the upper face of the halfway of the grip 4 and the cu  
 rling iron part 2, a finger putting curved plate 7 is provided fixedly, and  
 a guide 8 of an elliptical ring shape for coming into contact with and surro  
 unding the grip 5 is provided vertically. The maximum opening width of the u  
 pper and the lower grips 4, 5 is limited to about 10 degrees by trailing len  
 gth of the guide 8, and by only A motion of the gripping hand, the curling i  
 ron parts 2, 3 can be opened and closed. By allowing a treatment liquid such  
 as a permanent wave liquid, etc., to adhere to the groove 30 of the curling  
 iron part 3, a straight permanent 2 wave work can be executed easily and re  
 peatedly. COPYRIGHT: (C)1993,JPO&Japio

BEST AVAILABLE COPY

